

# ASHCOMBE OAK



**THICKNESS**

15mm

**WIDTH**

190mm

**LENGTH**

1900mm

**WEAR LAYER**

4mm

**PACK SIZE**

2.888m<sup>2</sup>

**PACK WEIGHT**

28.16kg



25-Year  
Warranty



Suitable for any domestic  
room, except bathrooms



Underfloor heating  
suitable

## PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Smooth
WOOD SPECIES	Oak	FINISH	UV Lacquered
PRODUCT ORIGIN	China	SHADE	Medium
BASE PLY	9mm Pine + 2mm Poplar	COLOUR	Natural
CONSTRUCTION	3-ply	GRADE	Rustic
PATTERN	Straight Plank	JOINING	Click
EDGE PROFILE	4-sides 0.5mm	INSTALLATION METHOD	Floating Floor - Click System

## TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	BS EN 717-1:2004	E1 (0.08mg/m3)
Slip Rating	N/A	N/A
Content of PCP	FD CEN/TR 14823:2006	PCP < 5 ppm
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m <sup>3</sup>

