

ASHDOWN OAK



THICKNESS

10mm

WIDTH

80mm

LENGTH

300mm

WEAR LAYER

3mm

PACK SIZE

0.96m²

PACK WEIGHT

6.5kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

| | | | |
|----------------|-------------------------|---------------------|----------------------|
| PRODUCT TYPE | Engineered Wood | SURFACE | Brushed |
| WOOD SPECIES | Oak | FINISH | UV Oiled |
| PRODUCT ORIGIN | China | SHADE | Medium |
| BASE PLY | Poplar + Eucalyptus | COLOUR | Golden |
| CONSTRUCTION | Multi-Ply | GRADE | Select |
| PATTERN | Herringbone/Parquet | JOINING | Tongue & Groove |
| EDGE PROFILE | 4-sides Micro 0.4-0.6mm | INSTALLATION METHOD | Nailed or Glued Down |

TECHNICAL INFORMATION

| TEST ITEM | TESTING METHOD | TEST RESULT |
|---------------------------------|------------------------------|-----------------------------|
| Release of Formaldayhyde | EN 717-1:2004-10 | < LOD (216 h)* (class E1) |
| Slip Rating | CNT/TS 15676:2007(D) | USRV22 |
| Content of PCP | CEN/TR 14823:2004 | PCP < 5 x 10-6n |
| Thermal Conductivity | BS EN ISO 10456:2007/AC:2009 | 0.16W/mK |
| Reaction to Fire Classification | BS EN14342:2013 | Dfl-s1 |
| Density Rating | - | 0.71-0.73 kg/m ³ |

