

AURORA OAK



THICKNESS

20mm

WIDTH

190mm

LENGTH

1900mm

WEAR LAYER

6mm

PACK SIZE

1.805m²

PACK WEIGHT

23.47kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

| | | | |
|----------------|---------------------|---------------------|--------------------------------|
| PRODUCT TYPE | Engineered Wood | SURFACE | Brushed |
| WOOD SPECIES | Oak | FINISH | UV Lacquered |
| PRODUCT ORIGIN | European Oak | SHADE | Light |
| BASE PLY | Poplar + Eucalyptus | COLOUR | Golden |
| CONSTRUCTION | Multi Ply | GRADE | Classic |
| PATTERN | Straight Plank | JOINING | Tongue & Groove |
| EDGE PROFILE | 2-sides 2mm | INSTALLATION METHOD | Floating, Nailed or Glued Down |

TECHNICAL INFORMATION

| TEST ITEM | TESTING METHOD | TEST RESULT |
|---------------------------------|------------------------------|-----------------------------|
| Release of Formaldayhyde | BS EN 717-1:2005 | E1 (0.2mg/m ³) |
| Slip Rating | CNT/TS 15676:2007(D) | USRV22 |
| Content of PCP | CEN/TR 14823:2004 | PCP < 5 x 10-6n |
| Thermal Conductivity | BS EN ISO 10456:2007/AC:2009 | 0.16W/mK |
| Reaction to Fire Classification | BS EN14342:2013 | Dfl-s1 |
| Density Rating | - | 0.71-0.73 kg/m ³ |

