

PRODUCT INFORMATION

PRODUCT DESCRIPTION	100% Waterproof Rigid core of stone plastic composite Click vinyl floor			
WEIGHT/ PACK	22kg	GLOSS	5-7%	
THICKNESS	Total 5(mm): 4(mm) with 0.5(mm) wearlayer + 1(mm) IXPE underlayment	DECO	Holkham Oak	
WIDTH			180(mm)	Cromer Oak
LENGTH			1220(mm)	Tankerton Oak

TECHNICAL INFORMATION

CHARACTERISTICS	TESTING METHOD	STANDARD REQUIREMENT	TESTING RESULT
Density	EN436	2000±100 (kg/m ³)	2096
Dimensional Stability Shrinking	EN434	L: ≤0.16%	0.03
		W: ≤0.16%	0.05
		Cupping: ≤1.0mm	0.5
Peeling Strength	EN434	≥70N/50mm	L:112 / W:105
Click Tension	EN684	Long Side: ≥175N/50mm	L: 305
		Short Side ≥175N/50mm	S: 312
Surface Scratch	ISO1518	≥2500g	2600
Dynamic Coefficient of Friction	EN13893:2002		0.35
TVOC	In compliance with CDPH/EHLB Standard Method V1.2-2017		≤0.5mg/m ³

CONSTRUCTION

