

PRODUCT INFORMATION

PRODUCT DESCRIPTION	100% Waterproof Rigid core of stone plastic composite Click vinyl floor (Herringbone)		
WEIGHT/ PACK	23.5kg	GLOSS	5-7%
THICKNESS	Total 6.5(mm): 5.5(mm) with 0.5(mm) wearlayer + 1(mm) IXPE underlayment	DECO	Kynance Oak
WIDTH			128(mm)
LENGTH	615(mm)		Marazion Oak

TECHNICAL INFORMATION

CHARACTERISTICS	TESTING METHOD	STANDARD REQUIREMENT	TESTING RESULT
Density	EN436	2000±100 (kg/m ³)	2098
Dimensional Stability Shrinking	EN434	L: ≤0.16%	0.06
		W: ≤0.16%	0.02
		Cupping: ≤1.0mm	0.3
Peeling Strength	EN431	≥70N/50mm	L:113 / W:89.3
Click Tension	EN684	Long Side: ≥175N/50mm	L: 285
		Short Side ≥175N/50mm	S: 308
Surface Scratch	ISO1518	≥2500g	2600
Dynamic Coefficient of Friction	EN13893:2002		0.35
TVOC	In compliance with CDPH/EHLB Standard Method V1.2-2017		≤0.5mg/m ³

CONSTRUCTION

