

CANNOCK OAK



THICKNESS

15mm

WIDTH

190mm

LENGTH

1900mm

WEAR LAYER

4mm

PACK SIZE

2.888m²

PACK WEIGHT

28.16kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Brushed
WOOD SPECIES	Oak	FINISH	UV Oiled
PRODUCT ORIGIN	China	SHADE	Light
BASE PLY	9mm Pine + 2mm Poplar	COLOUR	White Smoked
CONSTRUCTION	3-ply	GRADE	Rustic
PATTERN	Straight Plank	JOINING	Click
EDGE PROFILE	4-sides 0.5mm	INSTALLATION METHOD	Floating Floor - Click System

TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	BS EN 717-1:2004	E1 (0.08mg/m ³)
Slip Rating	N/A	N/A
Content of PCP	FD CEN/TR 14823:2006	PCP < 5 ppm
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m ³

