

DANSON OAK



THICKNESS

14mm

WIDTH

150mm

LENGTH

1900mm

WEAR LAYER

3mm

PACK SIZE

2.28m²

PACK WEIGHT

18kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Brushed
WOOD SPECIES	Oak	FINISH	UV Oiled
PRODUCT ORIGIN	European Oak	SHADE	Grey
BASE PLY	11mm Poplar + Eucalyptus	COLOUR	Grey Whitewashed
CONSTRUCTION	Multi-Ply	GRADE	Rustic
PATTERN	Straight Plank	JOINING	Tongue & Groove
EDGE PROFILE	4-sides 1mm	INSTALLATION METHOD	Floating, Nailed or Glued Down

TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldehyde	BS EN 717-1:2005	E1 (0.2mg/m ³)
Slip Rating	CNT/TS 15676:2007(D)	USR22
Content of PCP	CEN/TR 14823:2004	PCP < 5 x 10 ⁻⁶ n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m ³

