

DARWIN OAK



THICKNESS

14mm

WIDTH

190mm

LENGTH

1900mm

WEAR LAYER

3mm

PACK SIZE

2.166m²

PACK WEIGHT

18.95kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Brushed
WOOD SPECIES	Oak	FINISH	UV Oiled
PRODUCT ORIGIN	European Oak	SHADE	Medium
BASE PLY	Shorea SPP	COLOUR	Golden
CONSTRUCTION	Multi Ply	GRADE	Rustic
PATTERN	Straight Plank	JOINING	Tongue & Groove
EDGE PROFILE	2-sides 1.5mm	INSTALLATION METHOD	Floating, Nailed or Glued Down

TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	BS EN 14342:2013	E1 (0.2mg/m ³)
Slip Rating	CNT/TS 15676:2007(D)	USRV22
Content of PCP	FD CEN/TR 14823:2006	PCP < 5 ppm
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m ³

