

FULBOURN SOLID OAK



THICKNESS
18mm

WIDTH
150mm

LENGTH
300-1200mm

WEAR LAYER
N/A

PACK SIZE
1.44m²

PACK WEIGHT
19.55kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

PRODUCT TYPE	Solid Wood	SURFACE	Brushed & Handscraped
WOOD SPECIES	Oak	FINISH	UV Lacquered
PRODUCT ORIGIN	China	SHADE	Dark
BASE PLY	N/A	COLOUR	Coffee
CONSTRUCTION	Solid	GRADE	Select
PATTERN	Straight Plank	JOINING	Tongue & Groove
EDGE PROFILE	4-sides 0.5mm	INSTALLATION METHOD	Nailed or Glued Down

TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	BS EN 717-1:2004	E1 (0.08mg/m ³)
Slip Rating	N/A	N/A
Content of PCP	FD CEN/TR 14823:2006	PCP < 5 ppm
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m ³

