

GILLINGHAM OAK



THICKNESS

14mm

WIDTH

90mm

LENGTH

300mm

WEAR LAYER

3mm

PACK SIZE

1.512m²

PACK WEIGHT

12.5kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Brushed
WOOD SPECIES	Oak	FINISH	Invisible Oiled
PRODUCT ORIGIN	European Oak	SHADE	Light
BASE PLY	Poplar + Eucalyptus	COLOUR	Golden
CONSTRUCTION	Multi-Ply	GRADE	Select
PATTERN	Herringbone/Parquet	JOINING	Tongue & Groove
EDGE PROFILE	4-sides 0.5mm	INSTALLATION METHOD	Nailed or Glued Down

TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	EN 717-1:2004-10	< LOD (216 h)* (class E1)
Slip Rating	CNT/TS 15676:2007(D)	USRV22
Content of PCP	CEN/TR 14823:2004	PCP < 5 x 10-6n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m ³

