

PRODUCT INFORMATION					
PRODUCT DESCRIPTION	15mm Oak Engineered Multi-ply Flooring				
THICKNESS	15mm	WEAR-LAYER	4mm Oak	SURFACE	Smoked
WIDTH	90mm	BASE-PLY	11mm Eucalyptus		Brushed
LENGTH	400mm	PACK SIZE	1.872m ²		UV Oiled
WEIGHT/PACK	18.5kg	PALLET SIZE	52 boxes/plt		
JOINT METHOD	T&G	PATTERN	Herringbone		

TECHNICAL INFORMATION		
TEST ITEM	TESTING METHOD	TESTING RESULT
Release of Formaldehyde	EN717-1:2004	Class E1: ≤0.124 mg/m ³ air
Slip Resistance - Pendulum Test	EN14342:2013 Clause 4.6 & CEN/TS 15676:2007	Dry 42 / Wet 23
Thermal Conductivity	EN 14342:2013 Clause 4.7 & EN12664:2001 Heat Flow Meter Method	0.121W(m.k)
Thermal Resistance	EN 14342:2013 Clause 4.7 & EN12664:2001 Heat Flow Meter Method	Dfl-s1
COUNTRY OF ORIGIN	CERTIFICATION	HARDNESS RATING
Slovakia	FSC® (FSC-C 210380)	Top layer: Slovakia, Hardness: 1,120 lbf Base: China, Hardness: 1,420 lbf

SPECIFICATION DISCLAIMER

This technical data sheet was written by Canopy Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.



Canopy Flooring Co. V.2024