

# INGLEWOOD OAK



**THICKNESS**

10mm

**WIDTH**

125mm

**LENGTH**

300-1200mm

**WEAR LAYER**

2.5mm

**PACK SIZE**

2.4m<sup>2</sup>

**PACK WEIGHT**

15.6kg



25-Year  
Warranty



Suitable for any domestic  
room, except bathrooms



Underfloor heating  
suitable

## PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Brushed
WOOD SPECIES	Oak	FINISH	UV Oiled
PRODUCT ORIGIN	European Oak	SHADE	Medium
BASE PLY	8mm Poplar + Eucalyptus	COLOUR	Golden
CONSTRUCTION	Multi-ply	GRADE	Rustic
PATTERN	Straight Plank	JOINING	Tongue & Groove
EDGE PROFILE	4-sides 1mm	INSTALLATION METHOD	Floating, Nailed or Glued Down

## TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	BS EN 717-1:2005	E1 (0.2mg/m <sup>3</sup> )
Slip Rating	CNT/TS 15676:2007(D)	USRV22
Content of PCP	CEN/TR 14823:2004	PCP < 5 x 10 <sup>-6</sup> n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m <sup>3</sup>

