

KNIGHTON OAK



THICKNESS

10mm

WIDTH

125mm

LENGTH

300-1200mm

WEAR LAYER

2.5mm

PACK SIZE

2.4m²

PACK WEIGHT

17.5kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Brushed
WOOD SPECIES	Oak	FINISH	Lacquered
PRODUCT ORIGIN	European Oak	SHADE	Medium
BASE PLY	Eucalyptus	COLOUR	Golden
CONSTRUCTION	Multi Ply	GRADE	Rustic
PATTERN	Straight Plank	JOINING	Tongue & Groove
EDGE PROFILE	4-sides 1mm	INSTALLATION METHOD	Floating, Nailed or Glued Down
CERTIFICATION	FSC® Certified Flooring (FSC-C210380)		

TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	EN 717-1:2004-10	E1 (0.2mg/m3)
Slip Rating	CNT/TS 15676:2007(D)	USRV22
Content of PCP	CEN/TR 14823:2004	PCP < 5 x 10-6n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m ³

