

PRODUCT INFORMATION					
PRODUCT DESCRIPTION	20mm Oak Engineered Multi-ply Flooring				
THICKNESS	20mm	WEAR-LAYER	6mm Oak	SURFACE	Natural
WIDTH	190mm	BASE-PLY	14mm Eucalyptus		Brushed
LENGTH	1900mm	PACK SIZE	1.805m ²		UV Oiled
WEIGHT/PACK	24.5kg	PALLET SIZE	39 boxes/plt		
JOINT METHOD	T&G	PATTERN	Straight Plank		

TECHNICAL INFORMATION		
TEST ITEM	TESTING METHOD	TESTING RESULT
Release of Formaldehyde	EN717-1:2004	Class E1: ≤0.124 mg/m ³ air
Slip Resistance - Pendulum Test	EN14342:2013 Clause 4.6 & CEN/TS 15676:2007	Dry 42 / Wet 23
Thermal Conductivity	EN 14342:2013 Clause 4.7 & EN12664:2001 Heat Flow Meter Method	0.121W(m.k)
Thermal Resistance	EN 14342:2013 Clause 4.7 & EN12664:2001 Heat Flow Meter Method	Dfl-s1
COUNTRY OF ORIGIN	CERTIFICATION	HARDNESS RATING
Slovakia	FSC® (FSC-C 210380)	Top layer: Slovakia, Hardness: 1,120 lbf Base: China, Hardness: 1,420 lbf

SPECIFICATION DISCLAIMER

This technical data sheet was written by Canopy Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

