

# PARKHURST OAK



**THICKNESS**

14mm

**WIDTH**

125mm

**LENGTH**

300-1200mm

**WEAR LAYER**

3mm

**PACK SIZE**

1.8m<sup>2</sup>

**PACK WEIGHT**

16.38kg



25-Year  
Warranty



Suitable for any domestic  
room, except bathrooms



Underfloor heating  
suitable

## PRODUCT DETAILS

|                |                          |                     |                                |
|----------------|--------------------------|---------------------|--------------------------------|
| PRODUCT TYPE   | Engineered Wood          | SURFACE             | Brushed                        |
| WOOD SPECIES   | Oak                      | FINISH              | UV Lacquered                   |
| PRODUCT ORIGIN | European Oak             | SHADE               | Light                          |
| BASE PLY       | 11mm Poplar + Eucalyptus | COLOUR              | Natural                        |
| CONSTRUCTION   | Multi-ply                | GRADE               | Rustic                         |
| PATTERN        | Straight Plank           | JOINING             | Tongue & Groove                |
| EDGE PROFILE   | 4-sides 1mm              | INSTALLATION METHOD | Floating, Nailed or Glued Down |

## TECHNICAL INFORMATION

| TEST ITEM                       | TESTING METHOD               | TEST RESULT                 |
|---------------------------------|------------------------------|-----------------------------|
| Release of Formaldayhyde        | BS EN 717-1:2005             | E1 (0.2mg/m3)               |
| Slip Rating                     | CNT/TS 15676:2007(D)         | USRV22                      |
| Content of PCP                  | CEN/TR 14823:2004            | PCP < 5 x 10-6n             |
| Thermal Conductivity            | BS EN ISO 10456:2007/AC:2009 | 0.16W/mK                    |
| Reaction to Fire Classification | BS EN14342:2013              | Dfl-s1                      |
| Density Rating                  | -                            | 0.71-0.73 kg/m <sup>3</sup> |

