

PRODUCT INFORMATION					
PRODUCT DESCRIPTION	10mm Oak Engineered Multi-ply Flooring				
THICKNESS	10mm	WEAR-LAYER	2.5mm Oak	SURFACE	White
WIDTH	70mm	BASE-PLY	7.5mm Eucalyptus		Smoked
LENGTH	350mm	PACK SIZE	1.764m ²		Brushed
WEIGHT/PACK	13kg	PALLET SIZE	75 boxes/plt		UV Oiled
JOINT METHOD	T&G	PATTERN	Herringbone		

TECHNICAL INFORMATION		
TEST ITEM	TESTING METHOD	TESTING RESULT
Release of Formaldehyde	EN717-1:2004	Class E1: ≤0.124 mg/m ³ air
Slip Resistance - Pendulum Test	EN14342:2013 Clause 4.6 & CEN/TS 15676:2007	Dry 42 / Wet 23
Thermal Conductivity	EN 14342:2013 Clause 4.7 & EN12664:2001 Heat Flow Meter Method	0.121W(m.k)
Thermal Resistance	EN 14342:2013 Clause 4.7 & EN12664:2001 Heat Flow Meter Method	Dfl-s1
COUNTRY OF ORIGIN	CERTIFICATION	HARDNESS RATING
Slovakia	FSC® (FSC-C 210380)	Top layer: Slovakia, Hardness: 1,120 lbf Base: China, Hardness: 1,420 lbf

SPECIFICATION DISCLAIMER

This technical data sheet was written by Canopy Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

