

# SWINLEY OAK



**THICKNESS**

10mm

**WIDTH**

80mm

**LENGTH**

300mm

**WEAR LAYER**

3mm

**PACK SIZE**

0.96m<sup>2</sup>

**PACK WEIGHT**

6.5kg



25-Year  
Warranty



Suitable for any domestic  
room, except bathrooms



Underfloor heating  
suitable

## PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Smooth
WOOD SPECIES	Oak	FINISH	UV Lacquered
PRODUCT ORIGIN	China	SHADE	Medium
BASE PLY	Poplar + Eucalyptus	COLOUR	Golden
CONSTRUCTION	Multi-ply	GRADE	Select
PATTERN	Herringbone/Parquet	JOINING	Tongue & Groove
EDGE PROFILE	4-sides Micro 0.4-0.6mm	INSTALLATION METHOD	Nailed or Glued Down

## TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	EN 717-1:2004-10	< LOD (216 h)* (class E1)
Slip Rating	CNT/TS 15676:2007(D)	USR22
Content of PCP	CEN/TR 14823:2004	PCP < 5 x 10-6n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m <sup>3</sup>

