

UPTON OAK



THICKNESS

15mm

WIDTH

90mm

LENGTH

400mm

WEAR LAYER

4mm

PACK SIZE

1.872m²

PACK WEIGHT

13kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Brushed
WOOD SPECIES	Oak	FINISH	Lacquered
PRODUCT ORIGIN	European Oak	SHADE	Medium
BASE PLY	Poplar + Eucalyptus	COLOUR	Smoked
CONSTRUCTION	Multi Ply	GRADE	Select
PATTERN	Herringbone/Parquet	JOINING	Tongue & Groove
EDGE PROFILE	4-sides 0.5mm	INSTALLATION METHOD	Nailed or Glued Down

TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldehyde	EN 717-1:2004-10	< LOD (216 h)* (class E1)
Slip Rating	CNT/TS 15676:2007(D)	USR22
Content of PCP	CEN/TR 14823:2007	PCP < 5 x 10 ⁻⁶ n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m ³

