

WOODVALE OAK



THICKNESS

15mm

WIDTH

220mm

LENGTH

2200mm

WEAR LAYER

4mm

PACK SIZE

2.904m²

PACK WEIGHT

28kg



25-Year
Warranty



Suitable for any domestic
room, except bathrooms



Underfloor heating
suitable

PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Distressed & Handsanded
WOOD SPECIES	Oak	FINISH	Matt Lacquered
PRODUCT ORIGIN	European Oak	SHADE	Medium
BASE PLY	Poplar + Eucalyptus	COLOUR	Natural
CONSTRUCTION	Multi Ply	GRADE	Distressed
PATTERN	Straight Plank	JOINING	Tongue & Groove
EDGE PROFILE	4-sides 1mm	INSTALLATION METHOD	Floating, Nailed or Glued Down

TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	EN 717-1:2004-10	< LOD (216 h)* (class E1)
Slip Rating	CNT/TS 15676:2007(D)	USR22
Content of PCP	CEN/TR 14823:2004	PCP < 5 x 10-6n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m ³

