

# WYRE OAK



**THICKNESS**

14mm

**WIDTH**

190mm

**LENGTH**

1900mm

**WEAR LAYER**

3mm

**PACK SIZE**

2.166m<sup>2</sup>

**PACK WEIGHT**

19.71kg



25-Year  
Warranty



Suitable for any domestic  
room, except bathrooms



Underfloor heating  
suitable

## PRODUCT DETAILS

PRODUCT TYPE	Engineered Wood	SURFACE	Smooth
WOOD SPECIES	Oak	FINISH	Unfinished
PRODUCT ORIGIN	European Oak	SHADE	Light
BASE PLY	Poplar + Eucalyptus	COLOUR	Natural
CONSTRUCTION	Multi-Ply	GRADE	Rustic
PATTERN	Straight Plank	JOINING	Tongue & Groove
EDGE PROFILE	2-sides 1.5mm	INSTALLATION METHOD	Floating, Nailed or Glued Down

## TECHNICAL INFORMATION

TEST ITEM	TESTING METHOD	TEST RESULT
Release of Formaldayhyde	BS EN 717-1:2005	E1 (0.2mg/m3)
Slip Rating	CNT/TS 15676:2007(D)	USRV22
Content of PCP	CEN/TR 14823:2004	PCP < 5 x 10-6n
Thermal Conductivity	BS EN ISO 10456:2007/AC:2009	0.16W/mK
Reaction to Fire Classification	BS EN14342:2013	Dfl-s1
Density Rating	-	0.71-0.73 kg/m <sup>3</sup>

